

System Three S1 Clear Penetrating Epoxy Sealer

System Three's S1 Clear Penetrating Epoxy Sealer is a two part epoxy that seals wood effectively against moisture and oxygen, helping to protect your prized classic boat against one of its biggest foes, wood rot.

It is an excellent undercoat primer for most marine paints and clear finishes. S1 Sealer is ready to use with no thinning required. It can be applied by brush, roller, or spray between the temperatures of 59 to 104 degrees fahrenheit. A 2 gallon kit will treat about 300 to 350 square feet.



S1SEAL2GL System Three S1 2 Gallon Kit \$227

3M 6000 Series Half Facepiece Respirators

3M 6000 Series Half Facepiece Respirators are commonly used for stripping, sanding, painting, sealing, and for mixing and applying two part epoxy systems. Each of our halfpiece assembly includes: one face piece, one pair of 3M 6001 organic vapor cartridges, two pairs of 5P71 Particulate Prefilters, and one pair of 501 Particulate Filter Retainers. We also sell the replacement Organic Vapor [OV] cartridges for this respirator. Classic Boat Connection strongly recommends you use a respirator when working on restoring your boat.



3MRESPM 3M Respirator [medium] \$41
3MRESPL 3M Respirator [large] \$41
3MRESPC 3M Replacement OV Cartridge [pair] \$17

Smith's Tropical Hardwood Epoxy

Smith's Tropical Hardwood Epoxy glues any wood, hard or soft. Originally developed for marine applications, it will hold up to the constant beating and vibration common in everyday boat use. Due to a special wetting additive, oily woods, such as teak, need no special pretreatment beyond a fresh sand or saw-cut surface. When cured it will have a toughness and hardness comparable to hardwood while still remaining highly flexible, so as to distribute stress over a wider area. Smith's Epoxy Cleanup Solvent will dissolve and clean up excess Tropical Hardwood Epoxy before it is cured. Use only in temperatures above 50 degrees.



SMHDEPOXY Smith's Hardwood Epoxy 12oz \$28

Interlux Interprotect 2000E Barrier Coat

Interlux Interprotect 2000E is a two part self priming epoxy for protection against water absorption. It is used on bottoms after sealing them with two coats of a clear penetrating epoxy sealer. Apply 3 or 4 coats of Interlux Barrier Coat and allow it to cure 48 hours before applying your bottom paint. It helps your bottom planking from absorbing water and thus expanding and contracting.



INTEPOXY Interlux Interprotect 2000E \$122

Smith's Fill-It Epoxy Filler

Smith's Fill-It Epoxy Filler is a two part non-sag epoxy filler for the restoration of wood. It is easily sanded and cures overnight. Wood should first be prepared by cleaning and removing any loose finish, followed by sealing with a clear penetrating epoxy sealer. [a few hours drying time is necessary on sanded wood before application of filler]. Smith's Fill-It Epoxy Filler should dry to a full cure overnight with temperatures at 68 degrees and above.



SMFILL12OZ Smith's Epoxy Filler 12 oz Kit \$28

SMFILLQT Smith's Epoxy Filler QuartKit \$61

3M 5200

3M 5200 Mahogany polyurethane caulk is extremely strong and retains its strength above and below the waterline. It remains workable 4 hours after application, is tack free in 48 hours, and cures in 5 to 7 days. It stay flexible and allows for structural movement.

It is an extremely permanent caulk and should be used with some caution because it can be very difficult to remove.

3M5200M Mahogany 3M5200 Caulk [10 oz] \$25

3M5200MCASE Mahogany 3M5200 Caulk - Case of 12 \$285



Need restoration information for your project?

Our website has, torque sequences, engine specifications, Chris Craft propeller specs, detailed pictures of our windshield rubber, bowlight lenses and stern pole globes, in depth product information and much more.

We also feature internet specials for limited number items. Visit our website at:

classicboatconnection.com